

Speedgear Fluid FS 75W80 Z4

Speedgear Fluid FS 75W80 Z4 is a manual synthetic transmission oil with extended performance and high pressure resistance for special modern transmissions requiring ZF TE-ML 02L and MAN 341 Type Z4, providing extra high performance fuel economy and used in heavy-duty highway vehicles.

Usage

Recommended for all synchromesh gearboxes, including types with integrated retarder, and manual transmissions of heavy-duty vehicles, and can also be used in medium-duty manual gearboxes where mineral or synthetic gear oil is recommended.

Features

Excellent load carrying, anti-wear, and extreme pressure performance: Helps to protect against wear under harsh operating conditions.
Excellent protection: Helps to protect and to extend the life of synchronisers while delivering smoother shifting performance.
Effective protection at high operating temperatures: Contributes to extended drain and service intervals.
Excellent low-temperature fluidity: Contributes to easy and smooth shifting, and quick starts.

Technical Specifications

SAE Viscosity Class	-	75W80
Colour	Visual	Yellow
*Kinematic Viscosity @100 °C, cSt	ASTM D 445	9,7
*Viscosity Index	ASTM D 2270	155
*Flash point, °C	ASTM D 92	232
*Pour Point, °C	ASTM D 97	-39

**Data given above are typical properties and may vary slightly.*

Performance

MAN 341 Type Z4, ZF TE-ML 01L/02L/16K, API GL-4, MAN 341 Type E3, ZF TE-ML 08, Volvo 97307

Revision Number

01.11.2023 / REV02