

Super SPX

Super SPX is a gasoline engine oil produced by combining high-quality Group II and synthetic base oils suited to today's technology additives that meet ILSAC GF-5 & API SN performance.Can be used at API CF performanced diesel engine oil, too.

Features

Excellent Protection: It protects the engine against wear at high temperatures and ensures that the engine remains within the initial production tolerances.

High Engine Efficiency: It ensures the best efficiency from fuel and increases engine efficiency. It minimizes sediment formation.

Anti-Engine Wear: Prevents wear of the engine during the first start-up.

High Heat Oxidation and Foam Durability: While this product provides a long oil change interval, extends oil life. By neutralizing the resulting acid, it provides protection against the rust.Prevents abrasions with the foam control.

Technical Specifications

SAE Class	-	5W20	5W30	5W40	10W30	10W40
*Kinematic Viscosity @100˚C, cSt	ASTM D 445	7,68	10,85	13,88	10,31	14,46
*Viscosity Index	ASTM D 2270	152	153	173	137	146
*Colour	ASTM D 1500	2	2	2	2	2
*Flash Point, ˚C	ASTM D 92	228	226	232	226	232

**Data given above are typical properties and may vary slightly.*

Performance

API SN/SM/SL/CF ILSAC GF-5

Revision Number

01.05.2021 / REV02