

Super-Trak 15W40

Super-Trak 15W40 is a high quality four season engine oil blended for use in the crankcase of tractors and construction equipments.

Usage

Super-Trak 15W40 used in tractors diesel engines. Also, it is suitable to use in high performance products recommended for agriculture machines diesel engines.

Features

Corrosıon And Foam Stability: Thanks to its corrosion inhibitor, the engine is protected against engine rust and corrosion due to foam formation and therefore corrosion due to the foam cutting additive.

Prevent Formation of Sediment and Smut: When controlling the formation of sediments at high temperatures, the institution controls the dispersant properties of the control to prevent thickening of the oil.

Heat and Oxidation Durability: Provides a long oil change interval, extending oil life. Provides easy oil flow in cold climates.

High Cleaning Feature: The detergents and dispersants contained in it keep the engine parts clean.

Perfect Protection: Protects the engine against wear during high temperatures, prevents foam formation, allows the engine to remain within initial manufacturing tolerances

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	14.5
*Viscosity Index	ASTM D 2270	126
*Flash Point, °C	ASTM D 92	238

**Data given above are typical properties and may vary slightly.*

Performance

API CF-4 / SG

Revision Number

01.03.2019 / REV03