

Galaxy 10W40

Galaxy 10W40 is a semi synthetic multigrade engine oil formulated with the combination of high quality synthetic & paraffinic base oils and high performance additives to be used at API SL performanced gasoline & LPG engines and API CF performanced diesel engines.Provides better performance than mineral oils unique and extreme protection under all weather and driving conditions. DO NOT USE IN PARTICUL FILTERED ENGINES.

Usage

It is used safely in all gasoline & LPG and diesel passenger cars, turbocharged engines with catalytic converters. Recommended for light commercial vehicles with diesel engines required API CF performanced, too

Features

High Engine Efficiency: It provides the best efficiency from the fuel and increases the efficiency of the engine. It reduce the formation of sediments least.

Anti – Engine Wear: It prevents engine wear during initial operation.

Low exhaust Emissions: It Reduces exhaust emissions and helps to protect the environment.

Working at Low Temperature: Even at low temperatures, the first operation is easy and the engine life is extended.

Excellent Protection: It protects the engine against wear during high temperatures, allowing the engine to remain within the initial manufacturing tolerances.

Fuel Economy: It minimizes deposit formation which keeps the engine clear. Due to the lubrication process is excellent, it provides fuel economy.

High Corrosion and Foaming Durability: Thanks to its corrosion inhibitor within, the engine is protected against rust and corrosion and foam formation is prevented by the foam cutting additive, so the engine is protected against wear.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	14.2
*Viscosity Index	ASTM D 2270	144
*Flash Point, °C	ASTM D 92	240
*Pour Point, °C	ASTM D 97	-27

**Data given above are typical properties and may vary slightly.*

Performance

API SL/CF ACEA A3/ B4 MB 229.1 VW 501 01/505 00

Revision Number

03.03.2026 / REV04