

Gas Concrete Mould Oil

It is a specially formulated mould oil for gas concrete process by using superior additives and high quality base oils to prevent the adhesion of concrete to the mold.

Usage

It is used in gas concrete processes especially in the lubrication of large size gas concrete moulds applied by brushing and spraying.

Features

Film Layer Creation Feature: It forms a thin film layer inside the mold, preventing the sticking of the concrete to the mold.
Proper Surface Creation Feature: It provides smooth concrete surfaces.
There is No Mold Cleaning Problem: The mold removes the need for cleaning, allowing it to be used again.
Long Mold Life: It increases mold productivity and life span.
Ease of Application: It is ready to use and simple to apply.
Effective Protection Against Rust Formation: Eliminates the problem of rust in molds.

Technical Specifications

*Density, @15°C, gr/ml	ASTM D 4052	0,8821
*Kinematic Viscosity @100 °C, cSt	ASTM D 445	9,86
*Kinematic Viscosity @40 °C, cSt	ASTM D 445	82,2
*Viscosity Index	ASTM D 2270	98
*Flash Point, °C	ASTM D 92	240
*Pour Point, °C	ASTM D 97	-12

**Data given above are typical properties and may vary slightly.*

Revision Number

17.11.2026 / REV02