

SPD Hydraulic NFF / Low Temp Hydraulic Fluid

SPD Hydraulic NFF / Low Temp Hydraulic Fluid is a specially formulated non-freezing hydraulic oil to run trouble-free in hydraulic systems used in cold weather conditions. Contains synthetic base oils and superior performance additives.

Usage

Used in hydraulic systems used at cold weather conditions.

Features

High Corrosion Protection: Thanks to the corrosion inhibitor in additive system it is protective against corrosion.
Excellent Rust and Oxidation Resistance: Thanks to high oxidation resistance prevents rust, sediment formation and viscosity thickening caused by oxidation. Provides superior resistance against oxidation with its synthetic oil structure.
High Foam Control: Prevents foaming with its antifoam additive.
Excellent Anti-Wear Effect: Protects the system against abrasion by actively fulfilling the lubricating duty.
High Dispersant Feature: Provides efficient operation by preventing the formation of deposits with the help of dispersing additives in it.
Long Service Life: Used for a long time with the effect of synthetic and naphthenic base oils.

Technical Specifications

*Kinematic Viscosity @40˚C, cSt	ASTM D 445	30
*Viscosity Index	ASTM D 2270	140
*Flash Point, °C	ASTM D 92	254
*Pour Point, °C	ASTM D 97	-48

**Data given above are typical properties and may vary slightly.*

Performance

DENISON HF-0/1/2, CINCINNATI MILC-P68-P69-P70, T6C-020, DIN 51524 PART II, M - 2950 – S, AFNOR NF E 48-603, VICKERS I - 286 - S3, CETOP RP91H

Revision Number

01.11.2022 / REV05