

Generator Power HD 15W40

Generator Power HD 15W40 is a diesel engine oil specifically designed for generators, produced by combining paraffinic base oils with performance additives that meet today's technology standards.

Usage

Diesel generators are used in light commercial vehicles such as cars, vans, minibuses, and panel vans with turbo and superturbocharged engines, and in diesel engines where API CF-4 performance is required.

Features

Prevent Formation of Sediment and Smut: When controlling the formation of sediments at high temperatures, the institution controls with the dispersant property of the control, preventing the thickening of the oil, it balances the pressure.

High Corrosion and Foam Stability: It protects against engine rust and corrosion thanks to its corrosion inhibitör, prevents foam formation thanks to its foam cutter, therefore the engine is protected against wear.

High Heat and Oxidation Durability: It provides a long oil change interval and extends the oil life. Provides easy oil flow against cold climatic conditions.

High Cleaning Feature: The detergent and dispersant additives in it keep the engine parts clean.

Anti-wear feature: Prevents engine wear during first run.

Technical Specifications

*Kinematic Viscosity @100 °C, cSt	ASTM D 445	14,4
*Viscosity Index	ASTM D 2270	138
*Flash Point, °C	ASTM D 92	224
*Pour Point, °C	ASTM D 97	-24
*TBN, mgKOH/g	ASTM D 2896	11,2

**Data given above are typical properties and may vary slightly.*

Performance

API CF-4 ACEA E2 MTU TYPE 1 CAT TO 2 MB 228.0 MAN 270 Allison C3/C4

Revision Number

05.03.2026 / REV01