

Heat Process HF

Hot shaping rice and non-ferrous metals, especially for use in hot-pressing process, good film forming capacity at the base oil is formulated oil for metal forming.

Usage

Ball valves, pipe fittings, furniture accessories, such as brass railings title and non-ferrous metals as well as warm spread to the entire mold press as a lubricant and release agent used directly in the pressing process.

Features

Long Mould Life: HF Hotforming special formulation enables the use of longer mold to reduce the formation of the surface contamination.

Resistance Against Friction, High Production Performance: High-quality content in the solid lubricant, graphite is achieved thanks to efficient series production and reducing friction.

Low Smoked Effect: Download the smell of smoked and minimal levels during the pressing problems. It prevents the undesirable flammability because it has a high flash point. Thanks to its additives and high quality base oils and performs regularly in the best way the lubrication and cooling.

High Performance Cooling and Lubrication: Thanks to its additives and high quality base oils and performs regularly in the best way the lubrication and cooling.

Technical Specifications

Type	-	HF 101	HF 102
Colour	Visual	Black	Black
*Kinematic Viscosity @40°C, cSt	ASTM D 445	190	580
*Density, @15°C, gr/ml	ASTM D 4052	0,9012	0,9101
Flash Point, °C, min.	ASTM D 92	200	250

**Data given above are typical properties and may vary slightly.*

Revision Number

03.06.2026 / REV02