

SpeedCool Coolant Organik

Coolant Organic is the radiator fluid which anti-corrosion and anti-boiling property. It is suitable for use except the winter season.

Features

Excellent Protection in Hot Weather: it helps to prevent the boiling risk of engine coolant water.
Easy to Use: it is added to the radiator without adding water.
Strong Performance Against Rust and Corrosion Protection: The cooling system provides improved protection against rust and corrosion.
Long Engine Life: It provides excellent efficiency of the system's circulation pump. So the life of the engine is extended.

Technical Specifications

Colour	Visual	Yellow
*Density, 15°C, g/cm^3	ASTM D 4052	1,039
Boiling Point, ºC/ºF - Diluted with 50% - Undiluted Antifreeze	ASTM D 1120	 104 / 219 105 / 221
pH, 20°C; - Diluted with 50% - Undiluted Antifreeze	ASTM D 1287	 8,1 8,2
*Reserve Alkalinite, mL - Diluted with 50% - Undiluted Antifreeze	ASTM D 1121	 - 1,8
Freezing Point, ºC/ºF (ASTM D 1177)	Antifreeze Ratio (mL)	Water Ratio (mL)
-13 / 8,6	100	0
-11 / 12,2	90	10
-10 / 14	80	20
-7 / 19,5	70	30
-6 / 21	60	40
-5 / 23	50	50

Data given above are typical properties and may vary slightly.

Revision Number

10.11.2025 / REV05