SPEEDOL
Since 1921
Lubricants



50/50 Prediluted Organic Antifreeze (-40 ˚F) Coolant

50/50 Prediluted Organic Antifreeze (-40 ˚F) Coolant is a ready-to-use organic antifreeze containing mono ethylene glycol, demineralized pure water, high quality organic anti-corrosion additives and bitrex. It is biogradable and does not contain harmful borate, nitrite, nitrate, amine, phosphate and silicate.

Usage

It is especially recommended for aluminum alloy radiators and engines made of light metals. It can used in cast iron, steel body radiators and engines, too.

Technical Specifications

Freezing Point ºC / ºF (ASTM D 1177)	Antifreeze Ratio (mL)	Water Ratio (mL)
-40 / -40	%100	%0
-27 / -17	%80	%20
-13 / 9	%50	%50

**Data given above are typical properties and may vary slightly.*
***Use only fresh water. Do not use water from industrial processes. Do not use seawater or well water.*

Performance

BS 6580(GB), SAE J 1034(I), CUMA NC 956-16(I), FVV HEFT R 443(D), JIS K 2234(1)(J), UNE 26361-88(E), AFNOR R 15/601(1) (F), KSM 2142(K), EMPA(CH), ASTM D 3306/4985, NATO S 759, E/L 1415c, PORCHE/VW/AUDI/SEAT/SKODA TL 774 D/F, DTFR 29C110 (MB 325.3/2/1/0), FORD ESE M 97B49-A, CUMMINS 85T8-2(1), MAN 248, MAN 324 SNF, WARTSILIA 32-9011(C.W.), PEGASO, GM US 6277 M, RN 41-01-001, FORD WSS-M97B44-C, CHRYSLER MS 9176, MACK 014GS17004, MAN B&W D 36 5600, GM 1899 M(1), NAVİSTAR V-1, Volvo, FORD ESD M 97 B49-A, OPEL GM QL 130100, LEYLAND TRUCKS LTS 22 AF 10, JOHN DEERE H 24 B1 /C1, DEUTZ/MWN 0199-2091 2AUFLAGE, MACK 014GS 17004

Revision Number

16.12.2025 / REV02