

SpeedCool Anti-Freeze Longlife SGG40C G13 (Concentrate)

SpeedCool Anti-Freeze Longlife SGG40 is a pink-violet colored, high-corrosion protection concentrated coolant formulated specifically for use in all state-of-the-art radiators made of aluminum, cast iron, and magnesium alloys. It utilizes the long-lasting protection properties of low silicate and hybrid (Si-HOAT) organic acid technology (LoBrid). It is nitrite, amine, phosphate (NAP), and borate-free. It is more environmentally friendly than G12 series coolants.

Usage

It can be used diluted according to the refractometric protection grades specified in the table below. It is not recommended for lead, solder, or copper/brass radiators. For this group, the G12 organic type series is recommended.

Caution!
Dilute with pure or deionized water. Standard tap water has a different pH and chemical composition and may damage G13 antifreeze and the cooling system. Do not mix with any coolant other than G12++ type.

Technical Specifications

Colour	Visual	Pink-Violet
*Density, 15°C, g/cm^3	ASTM D 4052	1,135
Boiling Point, ºC/ºF - Diluted with 50% - Undiluted antifreeze	ASTM D 1120	 128 175
pH, 20°C, Undiluted antifreeze;	ASTM D 1287	8,6
Freezing Point, ºC/ºF (ASTM D 1177)	Antifreeze Ratio (ml)	Water Ratio (ml)
-	100	0
-35	50	50

Data given above are typical properties and may vary slightly.
***For dilutions, use only fresh water, prioritizing pure water. Do not use industrial process water. Do not use seawater or well water.*

Performance

Audi VW TL 774 J (Type G13)

Seat VW TL 774 J (Type G13)

Skoda VW TL 774 J (Type G13)

Revision Number

02.03.2026 / REV03