

2T Outboard Pro Oil

This is a water cooled gasoline marine engine oil blended with paraffinic based base oil refined using advanced technology and additives that increase engine protection, provides homogeneous mixture with gasoline.

Usage

Mixing Ratio Recommended by Engine Manufacturer	Amount of Product to Be Added to Gasoline
1 L	5 L
20:1	50 ml
25:1	40 ml
30:1	33 ml
32:1	31 ml
40:1	25 ml
50:1	20 ml
75:1	13 ml
100:1	10 ml

Features

Special Ashless Formulation: Thanks to its special ashless formulation, it prevents pollution in spark-plugs and early ignition.
High Rust and Corrosion Resistance: Thanks to its rust and corrosion inhibitor, successfully it protects bearings and gear surfaces against rust and corrosion.
Excellent Cleaning Feature: Prevents deposit formation in engine. Keeps the engine clean.
Eco Friendly: It does not harm the environment. It does not form oil layer on sea.
Excellent Lubrication and Cooling Feature: Provides excellent lubrication and prevents engine from heating.
High Thermal Stability: Thanks to its high thermal stability, it maintains its performance at high temperatures for a long time. Extends the life of the oil while maintaining a long oil change interval. Provides easy oil flow in cold climatic conditions.

Technical Specifications

*Kinematic Viscosity @100°C, cSt	ASTM D 445	7,2
*Viscosity Index	ASTM D 2270	154
*Flash Point, °C	ASTM D 92	70
*Pour Point, °C	ASTM D 97	-36

**Data given above are typical properties and may vary slightly.*

Performance

NMMA TC-W3

Revision Number

01.04.2019 / REV03