

Marine Outboard 4T 25W40

Marine Outboard 4T 25W40 is a synthetic blend gasoline marine engine oil for 4-stroke outboard engines and catalytic converters related sterndrives and inboard engines, compatible with NMMA FC-W performance, blended with additives that increase engine protection.

Usage

Marine Outboard 4T 25W40 can be used on outboard 4 stroke engines such as BOMBARDIER, MERCURY, YAMAHA, HONDA & NISSAN/TOHATSO and inboards and sterndrives such as VOLVO PENTA.

Features

High Rust and Corrosion Resistance: Thanks to its rust and corrosion inhibitor content, it protects the bearings and gear surfaces against rust and corrosion very successfully.It protects the engine that does not run during the winter season against corrosion at the maximum level.

Excellent Cleaning Feature: Thanks to its synthetic formulation, it provides high performance against oil reduction and piston pollution.

Eco-friendly: It does not harm the environment. This product does not create an oil layer on sea water. High Thermal Stability:Thanks to its high thermal stability, it maintains its performance at high temperatures for a long time.While providing a long oil change interval, it extends the life of the oil. Provides easy oil flow in cold climate conditions. It provides high resistance to abrasion at low temperatures. Protects valve systems.

Foam Stability: It has anti-foaming properties to prevent foaming and the entry of air bubbles into the oil chamber.

Technical Specifications

Appearance	Visual	Bright and Clear
*Colour	ASTM D 1500	2,5
*Kinematic Viscosity @100°C, cSt	ASTM D 445	13,50
*Viscosity Index	ASTM D 2270	108
*Pour Point, °C	ASTM D 97	-30

**Data given above are typical properties and may vary slightly.*

Performance

API SM, NMMA FC-W

Revision Number

11.11.2025 / REV01