

CSG Yellow Grease

CSG Yellow Grease is a yellow colored grease prepared by blending high quality base oils with calcium soap additives.

Usage

It provides quick and effective lubrication in a variety of applications areas where the operating temperature is not high. It is recommended for grease lubrication of hydraulic turbines, bearing and ball rolling bearings not exceeding 70°C. Provides superior performance in chassis oiling.

Features

High Resistance to Water and Corrosion: It provides high resistance to against the corrosion and water
Anti-Wear Feature: It minimizes the maintenance expense thereby decreasing the corrosion.
Not Leave of System Feature: It decreases the expenditures that stick on surface because of the fibrous structure.

Technical Specifications

Soap Type	-	Ca	Ca
Colour	Visual	Yellow	Yellow
NLGI	-	2	3
*Base Oil Viscosity @40°C, cSt	ASTM D 445	180-200	190-210
*Base Oil Viscosity @100°C, cSt	ASTM D 445	16-18	17-19
Dropping Point, °C, min.	TS 5937 ISO 6299	95	95
Worked Penetration @25°C	ASTM D 217	265-295	220-250
Operating Temperature, °C	-	-20 /+70	-20 / +70

**Data given above are typical properties and may vary slightly.*

Revision Number

11.12.2025 / REV09