

SHPD CNG 15W40

SHPD CNG 15W40 is a multigrade engine oil formulated by mixing high quality base oils and high-performance & low ash additives to use in CNG and LPG equipped vehicles.

Usage

It produced to use in natural gas engine, CNG's (compressed natural gas) commercial vehicles and LPG equipped vehicles.

Features

Low Ash, Excellent Cleanliness: With the low ash value extends the catalyst life.
High Engine Efficiency: It provides the best efficiency from the fuel and increases the efficiency of the engine. Sediment formation is most reduced.
Anti-Engine Wear: It prevents engine wear during initial operation.
Low Exhaust Emissions: It helps to protect the environment by reducing exhaust emission.
Excellent Protection, Foam Control: It protects the engine from wear during high temperatures, which prevents the formation of foams and provides the engine to remain within the initial manufacturing tolerances.
Fuel Economy: It minimizes deposit formation which keeps the engine clear. Due to the lubrication process is excellent, it provides fuel economy.
High Heat and Oxidation Durability: while this product provides a long oil change interval, extends oil life.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	13,87
*Viscosity Index	ASTM D 2270	134
*Pour Point, ˚C	ASTM D 97	-27
*Flash Point, ˚C	ASTM D 92	232

**Data given above are typical properties and may vary slightly.*

Performance

API CG-4 Man M 3271-1 MB 226.9 Volvo CNG

Revision Number

01.02.2017 / REV02