

Gama SS 5W30

Gama SS 5W30 is a multi-grade, semi-synthetic gasoline engine oil formulated for passenger car engines manufactured in 2003 and earlier where API SL/CF performance is required.

Usage

In addition to gasoline-powered vehicles, it can also be used in diesel engines, passenger cars, and LPG engines.**It is not suitable for vehicles with diesel particulate filter (DPF) technology.**

Features

Maximum Engine Power: It provides resistance against to friction which reduces the power of the engine by controlling wear and dirt.

Fuel Economy: It minimizes deposit formation which keeps the engine clear. Due to the lubrication process is excellent, it provides fuel economy.

Anti – engine wear: It prevents engine wear during initial operation.

Excellent Protection: It protects the engine against wear during high temperatures, allowing the engine to remain within the initial manufacturing tolerances.

High Corrosion and Foaming Durability: Thanks to the corrosion inhibitor inside, the engine is protected against rust and corrosion.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	10,53
*Viscosity Index	ASTM D 2270	156
*Flash Point, ˚C	ASTM D 92	222

**Data given above are typical properties and may vary slightly.*

Performance

API SL/CF

Revision Number

30.07.2026 / REV00