

Turbotex 20W60

Turbotex 20W60 is a diesel engine oil formulated with the combination of high quality paraffinic base oils and high performance additives. It is suitable to be used at super and turbo-charged engines of light commercial vehicles like passenger cars, pickup trucks, minibusses and vans.

Usage

Suitable to be used in turbo and super turbo charged engines of light commercial vehicles like cars, pick-up trucks, minibusses & vans and API CF-4 performanced diesel engines.

Features

Prevent Formation of Sediment and Smut: When controlling the formation of sediments at high temperatures, the institution controls with the dispersant property of the control, preventing the thickening of the oil, it balances the pressure.

High Corrosion and Foam Stability: It protects against engine rust and corrosion thanks to its corrosion inhibitör, prevents foam formation thanks to its foam cutter, therefore the engine is protected against wear.

High Heat and Oxidation Durability: It provides a long oil change interval and extends the oil life. Provides easy oil flow against cold climatic conditions.

High Cleaning Feature: The detergent and dispersant additives in it keep the engine parts clean.

Anti-wear feature: Prevents engine wear during first run.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	24
*Viscosity Index	ASTM D 2270	133
*Flash Point, ˚C	ASTM D 92	250

**Data given above are typical properties and may vary slightly.*

Performance

API CF-4 ACEA E2 MTU TYPE 1 MB 228.0 MAN 270 Allison C3/C4 CAT TO 2

Revision Number

03.03.2026 / REV04