

SPD Diesel HD 20W50

SPD Diesel HD 20W50 which meets API CF/SF performance is multigrade all season engine oil formulated with mixture of special high quality base oils and high performanced additives package to ensure excellent performance and service in diesel and gasoline engines.

Usage

SPD Diesel HD 20W50 is used in recommended vehicles for API CF class of diesel passenger vehicles and API SF class of gasoline vehicles.

Features

Anti – Engine Wear: Prevents engine wear during initial operation.

High Protection Capacity: Thanks to corrosion additives within prevents corrosion by forming a film on the metal surface.

High Corrosion Foam Stability: Thanks to corrosion inhibitor within, the engine is protected against rust and corrosion and foam formation is prevented by the foam cutting additive, so the engine is protected against wear.

High Heat and Oxidation Durability: While this product provides a long oil change interval, extends oil life. Provides easy oil flow in cold climatic conditions.

Performance of Sediment Formation Prevention: While controlling the formation of sediments at high temperatures, prevents the thickening of the oil while controlling the sediment control with the dispersant feature. Balances pressure. Maintenance costs are reduced.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	17,0
*Viscosity Index	ASTM D 2270	122
*Flash Point, ˚C	ASTM D 92	230
*Pour Point, °C	ASTM D 97	-21

**Data given above are typical properties and may vary slightly.*

Performance

API CF/SF

Revision Number

01.10.2019 / REV00