

SHPD GAS 15W40

SHPD GAS 15W40 is multigrade engine oil formulated by mixing high quality base oils and high-performance & additives to used in natural gas fueled engines of heavy commercial vehicles.

Usage

SHPD GAS 15W40 meets Cummins CES 20092 performance and performance requirements of many natural gas fueled engines.

Features

Low Ash, Excellent Cleanliness: With the low ash value extends the catalyst life.
High Engine Efficiency: It provides the best efficiency from the fuel and increases the efficiency of the engine. Sediment formation is most reduced.
Anti-Engine Wear: It prevents engine wear during initial operation.
Fuel Economy: It reduces oil consumption due to its low volatility.
High Heat and Oxidation Durability: While this product provides a long oil change interval, extends oil life.

Technical Specifications

*Density @15 °C, gr/ml	ASTM D 4052	0,8701
*Kinematic Viscosity @40˚C, cSt	ASTM D 445	115
*Kinematic Viscosity @100˚C, cSt	ASTM D 445	14,9
*Viscosity Index	ASTM D 2270	134
*Flash Point, ˚C	ASTM D 92	240
*Pour Point, ˚C	ASTM D 97	-39
*TBN, mgKOH/g	ASTM D 2896	7,5
*Sulfated Ash, %	ASTM D 874	0,91

**Data given above are typical properties and may vary slightly.*

Performance

API CF-4 CUMMINS CES 20092 CUMMINS CES 20085 DDC 93K216 MB- APPROVAL 226.9 MIL-L-2104F RENAULT RGD VOLVO CNG

Revision Number

13.07.2026 / REV04