

Galaxy 10W30

Galaxy 10W30 is a semi synthetic multigrade engine oil formulated with the combination of high quality synthetic & paraffinic base oils and high performance additives to be used at API SL performanced gasoline & LPG engines and API CF performanced diesel engines. Provides better performance than mineral oils unique and extreme protection under all weather and driving conditions. DO NOT USE IN PARTICUL FILTERED ENGINES.

Usage

It is used safely in all gasoline & LPG and diesel passenger cars, turbocharged engines with catalytic converters. Recommended for light commercial vehicles with diesel engines required API CF performanced, too.

Features

High Engine Efficiency: Ensures optimal fuel utilization and boosts engine efficiency. Minimizes deposit formation.

Anti-Wear: Prevents engine wear during cold starts.

Low Exhaust Emissions: Helps protect the environment by reducing exhaust emissions.

Low-Temperature Performance: Extends engine life by facilitating easy cold starts, even in low temperatures. Outperforms mineral oils, providing exceptional protection across all climate and road conditions.

Excellent Protection: Protects the engine against wear at high temperatures and helps maintain original manufacturing tolerances.

Fuel Economy: Minimizes deposit formation and keeps the engine clean; superior lubrication properties contribute to fuel efficiency.

High Thermal, Oxidation, and Foam Stability: Extends oil life and allows for longer oil change intervals. Neutralizes acids and protects against rust. Prevents wear through effective foam control.

Technical Specifications

*Kinematic Viscosity @100˚C, cSt	ASTM D 445	10.43
*Viscosity Index	ASTM D 2270	142
*Flash Point, °C	ASTM D 92	236
*Pour Point, °C	ASTM D 97	-27

**Data given above are typical properties and may vary slightly.*

Performance

API SL/CF ACEA A3/B4 MB 229.1 VW 501 01/505 00

Revision Number

24.09.2026 / REV04